

View Online at <https://aerobasegroup.com/nsn/2920-00-074-3616>

**Mounting Slot Width:**

0.280 inches

**Mounting Slot Length:**

0.380 inches

**Submersibility:**

Nonsubmersible

**Mounting Facility Spacing:**

1.750 in. C to c

**Voltage Rating:**

12.0 volts

**Closing Voltage Rating:**

Between 2.6 volts and 6.6 volts

**Opening Voltage Rating:**

Between 0.6 volts and 2.1 volts

**Pull-in Current:**

Between 52.6 amperes and 59.0 amperes

**Hold-in Current:**

Between 12.7 amperes and 14.3 amperes

**Plunger Stroke Length:**

0.812 inches

**Engaging Linkage:**

Not included

**Accommodated Linkage Threaded Hole Thread Size:**

1/2-13

**Contact Manual Closing Provision:**

Not included

**Control Terminal Quantity:**

2

**Control Terminal Type:**

Screw

**Grounded Control Terminal:**

Included

**Main Terminal Quantity:**

2

**Main Terminal Type:**

Stud

**Control Terminal Quantity Internally Connected To Main Terminal:**

1

**Motor Diameter For Which Rigid Mount Is Designed:**

5.560 inches

**Mounting Facility Type And Quantity:**

4 slot

**Surface Treatment:**

Cadmium

**Surface Treatment:**

Cadmium plated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T130-h