## NSN 2920-00-229-6512

Spark Plug - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/2920-00-229-6512

view offilite at https://defobasegroup.com/nsn/2520-00-225-0512
Body Style:
Electrically shielded, partial insulator, gasket seat
Dc Resistance Rating In Ohms:
10000.0
Reach Length:
0.375 inches
Usage Design:
Engine other than aircraft
Width Across Flats:
0.812 inches
Electrode Style:
Single flat shell ground electrode (see also style 4)
Thread Size And Series/type Designator And Location:
14-1.25mm base err-100
Mean Effective Pressure Rating:
Between 165.0 pounds per square inch and 185.0 pounds per square inch
Seat Major Diameter:
0.8125 inches
Height Above Mounting Surface:
2.781 inches
Top To Terminal Contact Distance:
1.000 inches
Top To Shield Thread Distance:
0.125 inches
Shield Thread Length:
0.375 inches
Barrel Inside Diameter:
0.468 inches
Terminal Sleeve Inside Diameter:
0.375 inches
Special Features:
Supports grumman a10 aircraft
Test Data Document:
81348-ws506 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
2 type and a class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## NSN 2920-00-229-6512

Spark Plug - Page 2 of 2



Fiig:

A10400