## NSN 3020-00-004-6403

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-004-6403

view Offilitie at https://aerobasegroup.com/nsi//sozo-oo-oooo
Outside Diameter:
Between 1.165 inches and 1.168 inches
Overall Length:
Between 1.138 inches and 1.142 inches
Bore Diameter:
0.375 inches
Bore Length:
Between 1.044 inches and 1.048 inches
Pitch Diameter:
1.194 inches
Face Width:
Between 0.559 inches and 0.565 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Not included
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Positive drive belt
Teeth Row Quantity:
1
Center To Center Distance Between Teeth Rows:
0.128 inches
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Tooth Pitch:
0.375 inches
Hub End Outside Diameter And Location:
0.695 inches aa end and 0.700 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.470 in the second and 0.400 in the second

0.479 inches aa end and 0.483 inches aa end

## **NSN 3020-00-004-6403** Sprocket Wheel - Page 2 of 2



Materiai:
Steel, qq-s-763, class 303, cond a
Material:
Steel comp 303
Material Specification:
Qq-s-763, class 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c