NSN 3040-00-193-8972

Thread Class: 2a both ends

Thread Direction:
Right-hand both ends
Thread Length:

Overall Length: 53.312 inches

0.375 inches both ends

0.750 inches both ends

Wrenching Facility Outside Diameter:

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-193-8972

Tip Length:
0.687 inches both ends
Shank Outside Diameter:
0.500 inches both ends
Shoulder Outside Diameter:
0.625 inches both ends
Groove Radius:
0.031 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Unc both ends
Core Diameter:
0.150 inches
Distance From End To Groove Center:
0.875 inches both ends
Thread Location:
External both ends
End Type:
Hexagon male both ends
End Connection Type:
Threaded external both ends
Groove Quantity:
1 both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Wrenching Facility Type:
Knurled surface both ends
Cross Section Size And Location:
0.187 inches diameter both ends

NSN 3040-00-193-8972

Flexible Shaft Assembly - Page 2 of 2



Casing Length Between Ferrules:
52.000 inches
Casing Outside Diameter:
0.406 inches
Casing Protective Device Type:
Rubber cover
Swivel End:
Provided both ends
Enddiameter:
2.031 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
53.312 inches
Core Rotation Direction:
Clockwise
Core Removability:
Nonremovable
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
No
Fiig:
Г246-е