NSN 3120-00-409-0105

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-409-0105

| Overall Length: Between 0.9400 inches and 0.9500 inches Body Outside Diameter: Between 0.9382 inches and 0.9386 inches Body Inside Diameter: Between 0.6250 inches and 0.6260 inches Corner Shape: Square all corners Hardness Rating: 40.0 rockwell c and 45.0 rockwell c |
|---|
| Body Outside Diameter: Between 0.9382 inches and 0.9386 inches Body Inside Diameter: Between 0.6250 inches and 0.6260 inches Corner Shape: Square all corners Hardness Rating: |
| Between 0.9382 inches and 0.9386 inches Body Inside Diameter: Between 0.6250 inches and 0.6260 inches Corner Shape: Square all corners Hardness Rating: |
| Body Inside Diameter: Between 0.6250 inches and 0.6260 inches Corner Shape: Square all corners Hardness Rating: |
| Between 0.6250 inches and 0.6260 inches Corner Shape: Square all corners Hardness Rating: |
| Corner Shape: Square all corners Hardness Rating: |
| Square all corners Hardness Rating: |
| Hardness Rating: |
| - |
| 40.0 rockwell c and 45.0 rockwell c |
| |
| Surface Finish: |
| 32.0 microinches outside diameter surface of body |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Mil-s-6049 military specification single material response |
| Surface Treatment: |
| Phosphate |
| Style Designator: |
| Solid, plain, no outside flanges |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-6049 spec. |