

View Online at <https://aerobasegroup.com/nsn/4140-00-535-6499>

Stage Quantity:

2

Speed Adjustments:

Single speed

Environmental Protection:

Corrosion resistant and humidity proof and moisture resistant and salt spray resistant and shock proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking and thermal protective device

Air Flow Rate:

35.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.125 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Three

Special Features:

Supplied w/an type connector and low pressure alarm switch; equipped w/4 discharge outlet tubes

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0