

View Online at <https://aerobasegroup.com/nsn/4140-00-609-9258>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

7.000 inches

**Length:**

9.375 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Moisture resistant

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5600.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

3.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking and safety impeller guard

**Air Flow Rate:**

245.000 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.250 horsepower

**Housing Inside Diameter:**

7.030 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-596 comp b federal specification single material response

**Quantity:**

1

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-7720, type iii military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-7720 spec.