

View Online at <https://aerobasegroup.com/nsn/4140-00-760-8131>

Stage Quantity:

2

Speed Adjustments:

Single speed

Length:

Between 5.090 inches and 6.000 inches

Flow Direction:

Inward

Environmental Protection:

Fungus proof and weatherproof

Ambient Temperature At Full Rated Power:

-18.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5600.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 12 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

310.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

95.0 watts

Housing Inside Diameter:

6.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.