

View Online at <https://aerobasegroup.com/nsn/4520-00-184-3707>

Heat Delivery Rate In Btu Per Hour:

648000.0

Ignition Method:

Automatic electrical

Current Type:

Ac

Pressure Rating:

15.0 pounds per square inch

Accessory Components And Quantity:

1 control, flame failure, 1 control, pressure limit, 1 cut-off, low water, 1 regulator, draft, 1 switch, excess stack temp

Furnished Items And Quantity:

1 feeder, water, 1 gage, steam pressure, 7 pipe, flue, 12 in. Diameter by 2 ft lg w/supports, tee, umbrella collar and cap, 1 circuit breaker, 1 valve, safety, steam pressure size, 1 water column assembly boiler, heating. Low pressure

Heating System Design:

Steam

Boiler Type:

Vertical fire tube

Firing Type:

Oil

Oil Burner Type:

Pressure atomizing

Oil For Which Designed:

No. Fs2, df1, df2 and jp-5 fuel oil

Jacket Inclosure Feature:

Included

Voltage In Volts:

115.0

Special Features:

Flue discharge outlet top of boiler, with lifting attachments, fungus and moisture treated, radio interference suppression, boiler opening steam 3 in. Min ips condensate return 2 in. Min ips

Material:

Steel

Specification Or Standard:

3 size and a style

Departure From Cited Designator:

As modified by special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T114-b