NSN 4720-00-006-6158

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-006-6158

Cross Sectional Shape:
Round
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.270 inches 2nd end
Outside Diameter:
0.922 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Angle Between Rigid Elbow Fittings In Deg:
90.0
Flange Outside Diameter:
1.500 inches 1st end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and outer layer spirally wrapped rubber fabric and 1st layer braided steel wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Flow Angle:
67.5 degrees 2nd end
Outer Covering Environmental Protection:
Cold resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
37.000 inches working
Flange Style:

i lalige otyle.

Round w/ out bolt holes 2nd end

NSN 4720-00-006-6158

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed	Media	For	Which	Design	ned
--------------------------	-------	-----	-------	--------	-----

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0