NSN 4820-00-089-2461

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-089-2461

Pipe Size Accommodated:
0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+2500.0 to 5000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Special Features:
W/handknob for adjusting relief pressure setting control cap rotated 90.0 deg. And additional washers provided on stem under handknob
control
Material:
Steel stem
Material Specification:
Astm a48, class 40 assn standard single material response seat
Media For Which Designed:
Oil, hydraulic single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-089-2461

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0