## NSN 5305-01-366-2783

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-366-2783

<b>-</b>
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.398 inches
Fastener Length:
Between 2.142 inches and 2.172 inches
Head Style:
Oval countersunk
Head Diameter:
Between 0.390 inches and 0.395 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.081 inches first hole
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
95000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.072 inches first hole and 2.098 inches first hole
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-366-2783

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0