## NSN 5306-00-003-4022



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-003-4022 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.296 inches and 0.357 inches **Fastener Length:** Between 0.868 inches and 0.909 inches **Head Style:** Hexagon **Head Height:** Between 0.120 inches and 0.140 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Hole Diameter:** 0.046 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.552 inches and 0.572 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hole Configuration Style:** Hexagon corners Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-00-003-4022

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0