

View Online at <https://aerobasegroup.com/nsn/5306-00-003-4159>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.511 inches and 0.687 inches

**Fastener Length:**

Between 2.349 inches and 2.369 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.282 inches and 0.297 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Grip Diameter:**

Between 0.5607 inches and 0.5616 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.562 inches and 1.578 inches

**Thread Qty Per Inch (tpi):**

18

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.224 inches first hole and 2.254 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

W/retaining element on shank

**Material:**

Steel

**Material Specification:**

Mil-b-83050 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-b-83050 spec.