

View Online at <https://aerobasegroup.com/nsn/5306-01-447-7824>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.240 inches and 0.250 inches

**Fastener Length:**

Between 0.302 inches and 0.312 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Hole Diameter:**

Between 0.076 inches and 0.077 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**End Application:**

F-15i

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.052 inches and 0.072 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Special Features:**

Requested name-bolt: altered item made from nas1304-1h

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams 6415 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.