

View Online at <https://aerobasegroup.com/nsn/5306-01-447-7940>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

Between 4.085 inches and 4.105 inches

**Head Style:**

Dished hexagon

**Head Height:**

0.110 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 3.765 inches and 3.785 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.931 inches first hole and 3.941 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Iron alloy 660

**Surface Treatment:**

Cadmium and chromate

**Thread Series Designator:**

Unjf

**Specification Data:**

80252-nas6703 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0