

View Online at <https://aerobasegroup.com/nsn/5310-00-186-0962>

Hole Diameter:

Between 0.679 inches and 0.694 inches

Outside Diameter:

Between 0.938 inches and 0.953 inches

Internal Prebent Key Length:

Between 0.063 inches and 0.094 inches

External Prebent Key Width:

Between 0.108 inches and 0.122 inches

Internal Prebent Key Width:

Between 0.110 inches and 0.120 inches

Overall Distance Including Keys:

1.328 inches

External Key Quantity:

11

Material Thickness:

Between 0.038 inches and 0.046 inches

End Application:

Main feed pumps, an/srn-2 (v) navigation radio set, mk 28, 5-inch 38 caliber twin gun mount, integrated target control system (itcs), an-tsw/10, teletype, model 28, fire pumps, tactical aircrew combat training sys (tacts), stream (std. Tensioned replenishment at sea method) , mk 38 gunfire control system, elevators, aircraft

Hardness Rating:

Between 50.0 rockwell b and 81.0 rockwell b

Material:

Steel comp 1115 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019

Material Specification:

Sae assn standard all material responses

Style Designator:

Key

Departure From Cited Designator:

As modified by internal prebent key length and internal prebent key width

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0