## NSN 5320-00-007-3325

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-007-3325



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.582 inches and 0.602 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.079 inches and 0.080 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

## Grip Length:

0.255 inches

Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.164 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjc

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-007-3325

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

