## NSN 5320-00-795-9363

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-795-9363

Through Observ
Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Hole Diameter:
Between 0.110 inches and 0.112 inches
Shank Diameter:
Between 0.166 inches and 0.169 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
Between 0.2794 inches and 0.2844 inches
Expansion Device:
Threaded sleeve
Grip Length:
0.312 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
125000 pounds per square inch
Thread Size:
0.112 inches
Countersink Angle:
100.0 degrees
Heat Treatment:
Annealed sleeve
Material:
Steel comp 431 expander
Material Specification:
Ams 5732 assn standard single material response bolt
Precious Material:
Silver
Surface Treatment:
Silver expander
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5320-00-795-9363

Blind Rivet - Page 2 of 2



Demi			

No

Fiig:

A040a0