NSN 5330-00-012-4932

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-012-4932

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| Between 0.150 inches and 0.170 inches |
| Overall Length: |
| Between 1.334 inches and 1.354 inches |
| Overall Width: |
| Between 1.334 inches and 1.354 inches |
| Aperture Diameter: |
| 0.875 inches |
| Outside Corner Radius: |
| 0.156 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| Between 1.021 inches and 1.041 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 1.021 inches and 1.041 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.156 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.156 inches |
| Cross-sectional Thickness: |
| 0.024 inches |
| Bolt Hole Quantity: |
| 4 |
| Hardness Rating: |
| 65.0 shore durometer a and 75.0 shore durometer a |
| Material: |
| Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu |
| Material Specification: |
| Astm d2000 2bg715 assn standard all material responses |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |