## NSN 5905-00-006-7099

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-006-7099		
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:		
-30.0 to 30.0		
Electrical Resistance:		
56.200 ohms		
Resistance Tolerance In Percent:		
-1.000 to 1.000		
Ambient Tempurature In Deg Celsius At Full Rated Power:		
25.0		
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:		
275.0		
Tempurature Range Of Tempurature Coefficient In Deg Celsius:		
-55.0 to 275.0		
Inclosure Method:		
Encased		
Terminal Type:		
Tab, solder lug		
Reliability Indicator:		
Established		
Reliability Failure Rate Level In Percent:		
0.010		
Terminal Length:		
Between 0.376 inches and 0.500 inches		
Body Length:		
Between 1.000 inches and 1.124 inches		
Body Width:		
Between 0.469 inches and 0.593 inches		
Body Height:		
Between 0.531 inches and 0.593 inches		
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:		
Between 0.709 inches and 0.729 inches		
Power Dissipation Rating In Watts:		
8.000 free air		
Err Default:		
0.140 inches		
Mounting Hole Size:		
Between 0.120 inches and 0.130 inches		
Cubic Measure:		
0.395 cubic inches		
Unpackaged Unit Weight:		

16.5 grams

Style Designator:

Axial terminal (s)

## NSN 5905-00-006-7099

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39009/2 gd	overnment specification
------------------------	-------------------------

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0