NSN 5905-00-011-7044

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-011-7044

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.218 inches
Body Diameter:
Between 0.484 inches and 0.516 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.344 inches and 0.406 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
Between 0.469 inches and 0.593 inches
Overall Diameter:
Between 0.484 inches and 0.516 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces
Nonturn Device Radius:
Between 0.240 inches and 0.250 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing w/panel seal
Electrical Resistance Per Section:

2.5 kilohms single section

NSN 5905-00-011-7044

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
Between 292.0 and 298.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: