## NSN 5905-00-060-1941

**Section Quantity:** 

Cylindrical bushing mounted

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-060-1941

| Reliability Indicator:                                    |
|---|
| Not established   |
| Overall Length:   |
| 1.250 inches  |
| Body Diameter:  |
| Between 1.100 inches and 1.310 inches                     |
| Shaft Diameter:   |
| Between 0.248 inches and 0.251 inches                     |
| Shaft Length:   |
| 0.875 inches  |
| Mounting Bushing Length:                                  |
| 0.500 inches  |
| Body Length:  |
| Between 0.578 inches and 0.672 inches                     |
| Shaft Style:  |
| Round, slotted  |
| Switch Type:  |
| Rotary  |
| Switch Voltage Rating In Volts:                           |
| 117.0   |
| Contact Arm Electrical Off Position:                      |
| Fully ccw   |
| Actuator Type:  |
| Single shaft  |
| Switch Operating Position:                                |
| Start of rotation   |
| Switch Contact Arrangement:                               |
| Single pole, single throw, normally closed                |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Locking bushing   |
|   |

**NSN 5905-00-060-1941**Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Features Provided:                             |  |
|--|--|
| Switch   |  |
| Electrical Resistance Per Section:             |  |
| 50.000 kilohms single section                  |  |
| Power Dissipation Rating Per Section In Watts: |  |
| 2.0 free air single section                    |  |
| Resistance Tolerance Per Section In Percent:   |  |
| 10.0 to 10.0 single section                    |  |
| Switch Current Type And Rating In Amps:        |  |
| 3.000 ac/dc                                    |  |
| Standard Taper Curve Per Section:              |  |
| A single section                               |  |
| Ferminal Type And Quantity:                    |  |
| 5 tab, solder lug                              |  |
| Shelf Life:                                    |  |
| N/a  |  |
| Jnit Of Measure:                               |  |
| -  |  |
| Demilitarization:                              |  |
| No   |  |
| Fiig:  |  |
| A002a0   |  |
|  |  |