## NSN 5905-00-072-7933

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-072-7933 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.560 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Body Length:** 0.725 inches **Overall Diameter:** 1.561 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 358.0 **Maximum Starting Torque:** 2.00 inch-ounces

**Maximum Running Torque:** 

2.00 inch-ounces

## NSN 5905-00-072-7933

Shaft End Play: 0.003 inches Shaft Runout:

Precision Nonwire Wound Variable Resistor - Page 2 of 3



0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
4 turret

## NSN 5905-00-072-7933

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0