NSN 5905-00-153-5731

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-153-5731

| Section Quantity: |
|-----------------------------------------------------------------------------|
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 0.535 inches |
| Terminal Length: |
| 0.155 inches |
| Overall Height: |
| 0.434 inches |
| Overall Width: |
| 0.298 inches |
| Body Length: |
| 0.380 inches |
| Body Width: |
| 0.298 inches |
| Body Height: |
| 0.434 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Maximum Running Torque: |
| 5.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.300 inches |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 100.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 270.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.150 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -150.0 to 150.0 single section |

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-153-5731

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|---------------------------------------------------------------------|
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |