

View Online at <https://aerobasegroup.com/nsn/5905-00-615-9064>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

2.8750 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

3.000 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

3.125 inches

**Angle Of Mounting Hole In Deg:**

90.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

90.0

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.750 inches

**Body Length:**

0.984 inches

**Mounting Lip Diameter:**

3.1250 inches

**Mounting Lip Depth:**

0.0620 inches

**Mounting Hole/stud Circle Diameter:**

0.875 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

354.5

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Power Dissipation Rating Per Section In Watts:**

8.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-1.0 to 1.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0