NSN 5905-01-170-1334

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-170-1334

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:							
-100.0/+100.0							
Electrical Resistance:							
11.000 kilohms							
Resistance Tolerance In Percent:							
-2.000/+2.000							
Ambient Tempurature In Deg Celsius At Full Rated Power:							
25.0							
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:							
150.0							
Tempurature Range Of Tempurature Coefficient In Deg Celsius:							
-55.0/+125.0							
Inclosure Method:							
Encapsulated							
Terminal Quantity:							
16							
Terminal Type:							
Tab, solder lug							
Reliability Indicator:							
Not established							
Terminal Length:							
Terminal Length: 0.160 inches							
-							
0.160 inches							
0.160 inches Body Length:							
0.160 inches Body Length: 0.650 inches							
0.160 inches Body Length: 0.650 inches Body Width:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width: 0.118 inches							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width: 0.118 inches End Application:							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width: 0.118 inches End Application: Common digitizer 2a (cd2a)							
0.160 inches Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width: 0.118 inches End Application: Common digitizer 2a (cd2a) Identical Value Resistor Quantity:							
Body Length: 0.650 inches Body Width: 0.250 inches Body Height: 0.164 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.250 total network Terminal Width: 0.118 inches End Application: Common digitizer 2a (cd2a) Identical Value Resistor Quantity: 15 each resistor							

N/a

NSN 5905-01-170-1334

Film Fixed Resistor Network - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A001a0