

View Online at <https://aerobasegroup.com/nsn/5915-00-013-9740>

**Overall Height:**

1.420 inches

**Body Length:**

2.000 inches

**Body Width:**

1.000 inches

**Body Height:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.600 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.600 inches

**Operating Temperature Range:**

+0.0 to 60.0 degrees celsius

**Reference Frequency Per Function:**

469.7 kilohertz blank

**Source Impedance Rating Per Function:**

2.2 kilohms blank

**Load Impedance Per Function:**

2.2 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.5 blank

**Functional Terminal Type And Quantity:**

3 pin output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

50.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

469.45 kilohertz blank and 469.68 kilohertz blank and 469.73 kilohertz blank and 469.95 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

469.68 kilohertz blank and 469.73 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0