## NSN 5930-00-004-6266

Sensitive Switch - Page 1 of 2

3 turret



View Online at https://aerobasegroup.com/nsn/5930-00-004-6266

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Driptight
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Body Length:
0.580 inches
Body Width:
0.200 inches
Body Height:
0.450 inches
Unthreaded Mounting Hole Diameter:
0.091 inches
Actuator Length:
0.479 inches
Actuator Style:
Leaf
Actuator Width:
0.090 inches
Actuator Free Position Height:
0.441 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
9.0 grams
Switch Actuating Force:
50.0 grams
Actuator Movement:
Between 0.065 pretravel inches and 0.014 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:

## NSN 5930-00-004-6266

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0