

View Online at <https://aerobasegroup.com/nsn/5930-00-005-3118>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.418 inches and 0.458 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Body Height:

0.513 inches

Switch Actuator Quantity:

1

Actuator Style:

Rectangular

Actuator Height:

Between 0.780 inches and 0.820 inches

Actuator Width:

Between 0.355 inches and 0.375 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0