NSN 5930-00-009-4577

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-009-4577

Thread Class:
2a Pada Stalas
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Watertight
Bushing Length:
0.430 inches
Body Length:
1.000 inches
Body Width:
0.810 inches
Body Height:
1.160 inches
Actuator Diameter:
0.323 inches
Actuator Height:
0.250 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 turret
Specification Data:

opcomoation bata

18876-11553700 manufacturers specification control

NSN 5930-00-009-4577

Push Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0