NSN 5930-01-025-0878

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-025-0878
Body Style:
Hole mounted
Overall Length:
0.863 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.823 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.493 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.660 inches
Actuator Style:
Loaf

Actuator Width:

0.130 inches

Actuator Free Position Height:

0.340 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole and slot

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 grams

Switch Actuating Force:

16.0 grams

Actuator Movement:

Between 0.340 pretravel inches and 0.019 overtravel inches and 0.014 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

NSN 5930-01-025-0878 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0