# NSN 5935-00-001-3157 Electrical Receptacle Connector - Pa



Electrical Neceptacle Confidence - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5935-00-001-3157
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.406 inches and 1.471 inches
Overall Height:
Between 0.929 inches and 0.945 inches
Overall Width:
Between 0.929 inches and 0.945 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.755 inches and 0.765 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.755 inches and 0.765 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
10-5 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
247.0 and 204.0 and 178.0 and 68.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
20

Thread Size:

0.625 inches

## NSN 5935-00-001-3157

Electrical Receptacle Connector - Page 2 of 2



_			 	
	Δrm	เทว	 Location	
	CIIII	ша	_ocalion	

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum

#### **Shell Surface Treatment:**

Cadmium

#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Shell Material Specification:**

Qq-a-367, comp 6061, temper t6 federal specification single material response

#### **Included Contact Quantity:**

5 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.025 gold grains, troy

#### **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Un

## **Specification Data:**

81349-mil-c-81511/21 government specification

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

#### Fiig:

A039b0

## Mil-std (military Standard):

•