NSN 5935-00-006-7093

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-006-7093 **Thread Class:** 2b **Thread Pitch Diameters:** +0.019 to 0.027 inches **Thread Direction:** Left-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 5.000 inches **Overall Diameter:** 2.062 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** B4s single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): 4 **Thread Size:**

1.562 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-006-7093

Electrical Plug Connector - Page 2 of 2



Contact Material: Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 3 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Special acme Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0