NSN 5935-00-233-6728

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-6728

| 9 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.969 inches |
| Overall Height: |
| 1.110 inches |
| Overall Width: |
| 0.891 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.130 inches |
| Distance Between Mounting Facility Centers: |
| 1.575 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "3, 10-20, 10-50" single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 6.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 250.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 250.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic phenolic single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Included Contact Quantity: |
| 3 single mating end single contact grouping |
| Included Contact Type: |
| Flat pin single mating end single contact grouping |

Contact surfaces gold

Precious Material And Location:

NSN 5935-00-233-6728

Electrical Receptacle Connector - Page 2 of 2



| Precious | Material | And | Weight: |
|----------|----------|-----|---------|
| | | | |

0.003 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0