

View Online at <https://aerobasegroup.com/nsn/5935-00-258-1093>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Wall type w/ or w/o cover

Overall Length:

10.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.250 inches

Overall Height:

9.062 inches

Overall Width:

5.750 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

5.250 inches

Cable Entrance Diameter:

1.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

B4s single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

60.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Conduit nut

Thready Qty Per Inch (tpi):

8

Thread Size:

3.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Metal

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Furnished items - chain

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0