## NSN 5935-00-549-1588

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-549-1588

view Offilite at https://defobasegroup.com/nsi//0305-00-043-1000
Body Style:
Straight shape
Overall Length:
Between 2.714 inches and 2.744 inches
Overall Height:
0.807 inches
Overall Width:
0.619 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
Between 2.495 inches and 2.505 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response

**Shell Material Specification:** 

Qq-s-698 federal specification single material response

## NSN 5935-00-549-1588

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-198833, ty gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

37 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.037 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-198833 spec.