## NSN 5935-01-133-7290

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-133-7290

| Body Style:   |
|---|
| Straight shape  |
| ·   |
| Overall Length: 1.213 inches  |
| Overall Width:  |
|   |
| 0.494 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.120 inches  |
| Distance Between Mounting Facility Centers:   |
| 0.984 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 9 single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Polarization Method:  |
| Mating end  |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Friction  |
| Terminal Location:  |
| Side single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and copper single mating end single contact grouping |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Terminal Type:  |
| Pin single mating end single contact grouping   |
| Shell Material:   |
| Steel   |
| Shell Surface Treatment:  |
| Cadmium and chromate  |
| Insert Material Specification:  |
| Mil-m-14, type sdg-f military specification single material response single mating end              |

Included Contact Quantity:

9 single mating end single contact grouping

## NSN 5935-01-133-7290

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.009 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):