NSN 5950-00-015-9520

Power Transformer - Page 1 of 2



| o |
|---|
| View Online at https://aerobasegroup.com/nsn/5950-00-015-9520 |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.375 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz single component and 430.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 1.938 inches |
| Body Width: |
| 1.812 inches |
| Body Height: |
| 2.750 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| |

2.0 amperes ac single component 1st secondary

Winding Operating Voltage:

3.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5950-00-015-9520

Power Transformer - Page 2 of 2



Fiig:

A058b0