## NSN 5962-01-091-9642

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-091-9642

View Online at https://aerobasegroup.com/nsn/5962-01-091-9642
Body Length:
0.390 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and externally compensated
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
D-4 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-22.0 volts power source and 22.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 printed circuit
Specification Data:
81349-mil-m-38510/101 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

**Fiig:** A458a0

Yes - demil/mli