## NSN 5970-00-177-1423

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-177-1423 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 2.260 inches after unrestricted recovery Main Body Inside Diameter: 2.190 inches as supplied **First Branch Inside Diameter:** 0.520 inches as supplied Main Body Wall Thickness: 0.180 inches after unrestricted recovery **First Branch Wall Thickness:** 0.060 inches after unrestricted recovery Main Bodylength: 7.110 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A22500