NSN 5985-00-007-9723

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-007-9723

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
8.590 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 4.340 inches and 4.400 inches
Overall Height:
3.170 inches
Overall Width:
2.180 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.220 inches and 1.280 inches
Operating Tempurature Range:
+0.0 to 55.0 degrees celsius
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
Bn or n
Mounting Facility Screw Thread Series Designator:
Iso s
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.3
Overall Attenuation Range In Decibels:
+5.0 to 35.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded hole
4 threaded hole
4 threaded hole Adjustment Device Type And Quantity:
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern:
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern: Four position rectangular
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms:
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms: 300.0 input
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms: 300.0 input Terminal Type And Quantity:
4 threaded hole Adjustment Device Type And Quantity: 1 electronic, current controlled Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms: 300.0 input Terminal Type And Quantity: 3 connector, coaxial, female

--

NSN 5985-00-007-9723

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0