NSN 5985-00-093-5544

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-093-5544

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.250 inches
Overall Height:
3.469 inches
Overall Width:
3.969 inches
Scale Linearity:
Linear
Scale Division Quantity:
15
Voltage Standing Wave Ratio:
3.50
Coaxial Connector Series Designation:
N .
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+59.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
59
Attenuation Per Step In Decibels:
1.0 and 10.0
Adjustment Device Type And Quantity:
2 slotted screw
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Test Data Document:
80063-9008064 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:Antennas, waveguides, and related equipment

Terminal Type And Quantity: 2 connector, coaxial, female

NSN 5985-00-093-5544

Variable Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0