NSN 5985-00-160-3820

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-160-3820

Application Design:
Printed circuit board
Body Style:
Cylindrical w/side terminals
Overall Length:
2.625 inches
Overall Width:
2.031 inches
Body Diameter:
1.625 inches
Scale Linearity:
Linear
Shaft Diameter:
0.250 inches
Bushing Length:
1.000 inches
Shaft Length:
1.500 inches
Body Length:
1.125 inches
Power Rating:
4.0 watts average and 15.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0 to 10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Overall Attenuation Accuracy In Decibels:
-1.00 to 1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
Mounting Facility Screw Thread Diameter: 0.375 inches

NSN 5985-00-160-3820

Variable Attenuator - Page 2 of 2



S	pe	cia	al F	-ea	ıtu	re	S
---	----	-----	------	-----	-----	----	---

Housing and shaft are steel; cadmium plating

Terminal Type And Quantity:

3 tab, solder lug

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0