NSN 5985-00-257-9484

Variable Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Style:

Cylindrical w/rear terminals



View Online at https://aerobasegroup.com/nsn/5985-00-257-9484

Overall Length:
3.063 inches
Shaft Diameter:
Between 0.247 inches and 0.249 inches
Shaft Length:
0.938 inches
Body Length:
2.125 inches
Overall Diameter:
2.749 inches
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-65.0/+175.0 degrees fahrenheit
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+29.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
30
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 70.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.145/+0.145
Mounting Thread Quantity:
32 per inch
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round

NSN 5985-00-257-9484

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

75.0 input-output

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0