## NSN 5985-01-180-4099

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-180-4099

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.880 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches
Overall Height:
1.900 inches
Overall Width:
2.560 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches
End Application:
An/alq-122/b52
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc and sma
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

## NSN 5985-01-180-4099

Variable Attenuator - Page 2 of 2



Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Four position diamond
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A223a0