## NSN 5990-00-018-9721

Differential Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-018-9721

| Body Material:  |
|---|
| Steel, stainless  |
| Body Style:   |
| Standard round d  |
| Shoulder Diameter:  |
| Between 1.9850 inches and 1.9900 inches                   |
| Pilot Diameter:   |
| 0.5950 inches   |
| Second Shoulder Diameter:                                 |
| Between 1.9985 inches and 1.9995 inches                   |
| Second Shoulder Length:                                   |
| 0.1700 inches   |
| Overall Length:   |
| 4.5490 inches   |
| Flange Diameter:  |
| Between 2.2490 inches and 2.2500 inches                   |
| Flange Thickness:   |
| 0.2500 inches   |
| Body Diameter:  |
| 1.9900 inches   |
| Shaft Diameter:   |
| 0.2403 inches single shaft and 0.2405 inches single shaft |
| Shaft Length:   |
| 0.7190 inches single shaft                                |
| Maximum Tempurature Rise:                                 |
| 25.0 degrees celsius                                      |
| Body Size:  |
| 23  |
| Stator Input Voltage Rating In Volts:                     |
| 90.0  |
| Stator Input Current Rating:                              |
| 215.0 milliamperes  |
| Stator Input Electrical Power Rating:                     |
| 4.8 watts   |
| Frequency In Hertz:                                       |
| 60.0  |
| Zso Impedance Magnitude In Ohms:                          |
| Between 370.00 and 460.00                                 |
| Zso Impedance Angle In Deg:                               |
| Between 74.00 and 78.00                                   |

Between 175.00 and 220.00

**Zrs Impedance Magnitude In Ohms:** 

## NSN 5990-00-018-9721

Differential Transmitter Synchro - Page 2 of 3



| Zrs Impedance Angle In Deg:                      |
|--|
| Between 15.00 and 20.00                          |
| Phase Shift Angle In Deg:                        |
| 11.500 input to output                           |
| Electrical Error Angular Range In Minutes:       |
| -6.0 to 6.0                                      |
| Spline Tooth Quantity:                           |
| 22 single shaft                                  |
| Actuator Friction Torque At Plus 25 Deg Celsius: |
| 0.20 inch-ounces                                 |
| Torque Gradient Per Angular Deg:                 |
| 0.030 inch-ounces                                |
| Shaft Radial Play Test Point:                    |
| 0.125 inches                                     |
| Shaft Maximum Radial Play:                       |
| 0.0010 inches                                    |
| Shaft End Play:                                  |
| 0.0025 inches                                    |
| Pilot Length:                                    |
| 0.0430 inches                                    |
| Shoulder Length:                                 |
| 0.2500 inches                                    |
| Aft Of First Flange Diameter:                    |
| Between 1.9985 inches and 1.9995 inches          |
| Mounting Surface To Terminal End Distance:       |
| 3.8300 inches                                    |
| Spline Tooth Diametral Pitch:                    |
| 96 single shaft                                  |
| Shaft Maximum Runout:                            |
| 0.0008 inches                                    |
| Shaft Thread Series Designator:                  |
| Unf single shaft                                 |
| Shaft Thread Direction:                          |
| Right-hand single shaft                          |
| Shaft Thread Class:                              |
| 2a single shaft                                  |
| Terminal Location:                               |
| Rear   |
| Shaft Thread Length:                             |
| 0.2900 inches single shaft                       |
| Shaft Type:                                      |
| Spline w/threads single shaft                    |
| Transformation Ratio:                            |
|  |

1.154 rotor to stator

## NSN 5990-00-018-9721

**Shaft Thread Size:** 

**Fiig:** A07800

Differential Transmitter Synchro - Page 3 of 3



| 0.250 inches single shaft  |
|--|
| Shaft Radial Play Determining Weight:  |
| 8.0 ounces   |
| Shaft End Play Determining Weight:   |
| 16.0 ounces  |
| Test Data Document:  |
| 81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 6 screw  |
| Specification Data:  |
| 81349-mil-s-20708/55 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |