

View Online at <https://aerobasegroup.com/nsn/6240-00-722-6467>

Overall Length:

0.630 inches

Filament Designation:

C-2f

Light Output Rating:

0.004 spherical candlepower single rating

Average Life Rating In Hours:

50000.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Nimitz class cvn; forrestal class cv; defense communications radio (9 systems); virginia class cg (41); teletype, model 28; landing system automatic carrier, dual channel; spruance class dd(963); deep submergence systems programs (dssp); los angeles class ssn (688); ticonderoga class cg (47); aircraft, tomcat f-14; aircraft, viking s-3b; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search & rescue, hh-60j

Emitted Light Characteristic:

Colorless

Light Center Length:

0.380 inches

Voltage Rating:

10.000 volts

Wattage Rating:

0.120 watts and 0.150 watts

Base Style:

Single contact miniature flanged

Bulb Style:

T (tubular)

Bulb Designator:

T-1 3/4

Bulb Light Transmission Characteristic:

Transparent

Current Rating For Which Designed:

Between 0.012 amperes and 0.015 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07900