NSN 6625-00-189-3838

Ammeter - Page 1 of 2

1500.0

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-189-3838

| Overall Length: |
|---|
| 3.500 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Overall Diameter: |
| 2.250 inches |
| Environmental Protection: |
| Dust resistant |
| Furnished Items And Quantity: |
| Clamp 1 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Sensitivity Rating: |
| 1900.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Acquirocy In Parcents |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| • |
| -2.0 to 2.0 at full scale single indicator single range |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Power Source: |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Power Source: External |
| -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 0.750 inches Meter Body Diameter Behind Mounting Flange: Between 2.022 inches and 2.037 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: |

-20.0 to 20.0 amperes, dc single indicator single range

Measurement Range:

NSN 6625-00-189-3838

Ammeter - Page 2 of 2



| Scale Selection Method: |
|---|
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |