NSN 6625-00-272-9928

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-272-9928

| view Online at https://aerobasegroup.com/hsh/6625-00-272-9926 |
|--------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Current For Which Designed: |
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 2.062 inches |
| Scale Division Quantity: |
| 30 single indicator single range |
| Overall Diameter: |
| 2.187 inches |
| Environmental Protection: |
| Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and |
| water resistant |
| Distance Between Mounting Facility Centers: |
| 1.187 inches |
| End Application: |
| Aircraft phantom f-4, hercules c-130, awacs e-3a, support equipment aircraft ov-10a, c-5, t-37, f-106, t-38, b-52 |
| Furnished Items And Quantity: |
| Nut 2; lockwasher 2; seal 1 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Two hole/stud |
| Sensitivity Rating: |
| 21.0 millivolts |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.750 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.000 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Beelenseyed Colors |

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

NSN 6625-00-272-9928

Ammeter - Page 2 of 2



| Mounting Facility Type And Quantity: |
|-------------------------------------------------------|
| 1 clamp |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| -30.0/+30.0 amperes, dc single indicator single range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Knife edge pointer |
| Criticality Code Justification: |
| Feat |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized, weapon system essential |
| Special Markings: |
| On front, -; +; onback, 2.867768 |
| Material: |
| Aluminum |
| Surface Treatment: |
| Paint |
| Special Test Features: |
| Complies with mil-m-10304 |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A310a0 |